



BEST AVAILABLE COPY

PET/GB04/3249



INVESTOR IN PEOPLE

The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ

**PRIORITY
DOCUMENT**

SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH RULE 17.1(a) OR (b)

RECEIVED

16 AUG 2004

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

I also certify that the attached copy of the request for grant of a Patent (Form 1/77) bears an amendment, effected by this office, following a request by the applicant and agreed to by the Comptroller-General.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

Signed

H. Behan

Dated

6 August 2004

28 JUL 2003

NEWPORT



28JUL03 E825880-2 C80537
P01/7700 0.00-0317615.3

Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

The Patent Office

Cardiff Road
Newport
South Wales
NP10 8QQ

1. Your reference

500 Proximity

2. Patent application number

(The Patent Office will fill in this part)

0317615.3

28 JUL 2003

3. Full name, address and postcode of the or of each applicant (underline all surnames)

Stannah Stairlifts Limited
Watt Close
East Portway
ANDOVER
Hampshire SP10 3SD

Patents ADP number (if you know it)

If the applicant is a corporate body, give the country/state of its incorporation

England

5650239001

4. Title of the invention

IMPROVEMENTS IN OR RELATING TO
STAIRLIFTS

5. Name of your agent (if you have one)

"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)

~~Ipca Consulting Limited~~ ~~URQUHART-DYKES & LORD~~
~~Northpoint House~~
~~52 High Street~~
~~Knaphill~~
~~Surrey GU21 2PY~~
ALEXANDRA HOUSE
1 ALEXANDRA ROAD
SWANSEA
SA1 5ED

Patents ADP number (if you know it)

7423692002 08857153001

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number

Country

Priority application number
(if you know it)

Date of filing
(day / month / year)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing
(day / month / year)

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if:

- a) any applicant named in part 3 is not an inventor, or
 - b) there is an inventor who is not named as an applicant, or
 - c) any named applicant is a corporate body.
- See note (d))

Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form

Description 9

Claim(s) 3

Abstract 1

Drawing(s) 3 + 3 *ph*

10. If you are also filing any of the following, state how many against each item.

Priority documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (*Patents Form 7/77*)

Request for preliminary examination and search (*Patents Form 9/77*)

Request for substantive examination (*Patents Form 10/77*)

Any other documents
(please specify)

11. I/We request the grant of a patent on the basis of this application.

Signature

Andrew Harris

Date

25.07.2003

12. Name and daytime telephone number of person to contact in the United Kingdom

Andrew Harris 01483 489818

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 08459 500505.*
- Write your answers in capital letters using black ink or you may type them.*
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.*
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.*
- Once you have filled in the form you must remember to sign and date it.*
- For details of the fee and ways to pay please contact the Patent Office.*

Patents Form 1/77

IMPROVEMENTS IN OR RELATING TO STAIRLIFTS

Field of the Invention

This invention relates to stairlifts and, in particular, to a method of and/or apparatus for enhancing the safety of a stairlift installation. Whilst the invention has been devised, in particular, for incorporation into curved stairlifts, some aspects of the invention are also applicable to straight stairlifts.

Background to the Invention

Most stairlift installations include remote call switches mounted at the top and bottom of the stairlift rail. These allow a user to send a call signal to the stairlift in the event that the stairlift carriage is parked at the opposite end of the staircase. In such an instance, the user operating the call switch at a remote location may not be aware of a second user attempting to mount, or dismount from, the stairlift chair. In the case of a curved stairlift, for example, a person standing at one end of the staircase may not be able to see the opposite end of the staircase.

Current stairlift designs typically incorporate a carriage holding switch mounted on an armrest of the chair. When in the 'off' position this switch ensures that the stairlift cannot be operated and, when a user is mounting, or dismounting from the stairlift, the stairlift will not move if a call is made to the stairlift from one the remote call switches.

Carriage holding switches on existing stairlift installations are a constant source of inconvenience and/or confusion. Users are instructed to move the switch to the 'off' position, at the end of each journey, so that the carriage cannot be moved whilst the user dismounts. The user is further instructed to move the switch to the 'on' position, after dismounting, so that the empty chair may be moved under the control of the

remote call switches. The switch must then be moved to the 'off' position again, for mounting. Given that typical users of stairlifts are elderly, to some extent physically incapacitated, and often easily confused, the need to constantly re-position the carriage holding switch often results in the correct procedure not being adopted. In some instances the carriage holding switch will not be turned off when dismounting the chair. This exposes a user to risk. In other instances, the switch may be left 'off' when the chair is empty, thus causing inconvenience to a second user attempting to call the carriage using one of the remote call switches. A further problem with the existing carriage holding switches is that we have observed a tendency amongst some such users to assume that the stairlift is either not working correctly, or broken down, if the carriage holding switch has been inadvertently left in the 'off' position. This leads to unnecessary service call-outs.

It is an object of this invention to provide a method of and/or means for controlling the operation of a stairlift which will go at least somewhat in addressing the aforementioned problems; or which will at least provide a novel and useful choice.

Summary of the Invention

Accordingly, in a first aspect, the invention provides a method of enhancing the safety of a stairlift assembly having:-

a rail extending between an upper end and a lower end of a staircase;

a carriage moveable along said rail;

carriage operating controls remote from said carriage;

said method being characterised in that a proximity sensor is provided which is operable to sense a person in the proximity of said carriage, and to render said carriage operating controls inoperative.

Preferably said method includes providing said proximity sensor on or about said carriage.

Preferably a chair is mounted on said carriage, said method further including providing an occupancy sensor to sense when a user is seated on said chair.

Preferably said chair is foldable, said method further including a sensor to sense when said chair is in the folded configuration.

In a second aspect the invention comprises a stairlift installation having:

a rail extending between an upper and lower end of a staircase;

a carriage moveable along said rail; and

carriage operating controls remote from said carriage,

said apparatus being characterised in that a proximity sensor is provided, said proximity sensor being operable to sense the proximity of a person to said carriage and being further operable to, in the event of sensing such a person, rendering said carriage operating controls inoperative.

Preferably said proximity sensor is mounted on or about said carriage.

Preferably said installation further includes a chair mounted on said carriage, part of said proximity sensor being mounted on said chair.

Preferably said proximity sensor is of the capacitance type.

Preferably said installation further includes a load sensor operable to detect the presence of a user seated in said chair.

Preferably said chair is foldable, said installation further including a position sensor operable to sense when said chair is in the folder configuration.

In a third aspect the invention provides a stairlift assembly including:

a rail

a carriage mounted on said rail for movement there-along;

a chair mounted on said carriage;

at least one user operable control to cause movement of said carriage along said rail,

said assembly being characterised in that an occupancy sensor is provided to sense the presence of a user seated in said chair and to activate said user operable control only when a user is seated in said chair.

Preferably said occupancy sensor comprises a load sensor incorporated in said chair and/or carriage.

Many variations in the way the present invention can be performed will present themselves to those skilled in the art. The description which follows is intended as an illustration only of one means of performing the invention and the lack of description of variants or equivalents should not be regarded as limiting. Wherever possible, a

description of a specific element should be deemed to include any and all equivalents thereof whether in existence now or in the future. The scope of the invention should be limited by the appended claims alone.

Brief Description of the Drawings

One preferred form of the invention will now be described with reference to the accompanying drawings in which:

- Figure 1: shows a plan view of a typical curved stairlift installation;
- Figure 2: shows an isometric view of a stairlift carriage and chair including various components which contribute to the present invention;
- Figure 3: shows, diagrammatically, the operation of a stairlift installation according to the invention with a user standing in proximity to the chair and carriage;
- Figure 4: shows a similar view to figure 3 but with the user mounting, or dismounting from, the stairlift chair; and
- Figure 5: shows a similar view to figures 3 and 4 but with the user folding or unfolding the chair.

Detailed Description of Working Embodiment

Referring firstly to Figure 1, the invention provides a method of and/or means for, enhancing safety of a stairlift installation mounted in staircase 10. In the form shown

the staircase has an upper end 12, a lower end 14 and an intermediate landing 16. In accordance with conventional practice, a stairlift rail 18 is mounted to one side of the staircase and extends between the upper end 12 and lower end 14. A stairlift carriage and chair assembly 20 is mounted on the rail 18 for movement along the rail between the ends 12 and 14.

Also in accordance with conventional practice, landing controls or call switches 22 and 24 are provided on the staircase walls at or adjacent to the upper end 12 and lower end 14 respectively of the staircase. These landing switches, which could also be portable hand-held units, allow for a user to send a call signal to the stairlift in the event the carriage/chair 20 is parked at a location remote from the switch being activated. Thus, as illustrated in Figure 1, operation of the control 24 would be used to call the carriage and chair to the lower end 14 of the staircase.

It will be appreciated that a person or user, located at the lower end 14 of the staircase illustrated in Figure 1, would be unable to see the carriage and chair 20. Thus, if the carriage holding switch on the chair 20 were in the 'on' position, and a user was attempting to mount or dismount from the chair 20, any motion of the carriage induced by operation of switch 24 would be undesirable.

In accordance with one aspect of the invention a proximity sensor is provided to sense the proximity of a user to the carriage. In the event close proximity is detected, the controls 22 and 24 are rendered inoperative.

The proximity sensor is preferably included in the carriage/chair 20 but could be mounted in some other position on the staircase and be aligned and programmed to detect the proximity of a person to the carriage. By way of example, the proximity sensor is preferably of the capacitance type which uses an antenna/electrode to detect change in capacitance. As will be appreciated, such a system detects the difference in

capacitance between the antenna and a user. The standard system consists of an antenna and a control circuit, the control circuit detecting the difference in capacitance between the antenna and any object within proximity. The control circuit typically further includes a sensitivity capacitor connected to the antenna and a control board which allows the sensitivity of the sensor to be altered by adjusting the value of the capacitor. If desired the control circuit may be configured such that it sends out a 'heartbeat' signal allowing the health of the device to be monitored by the main stairlift control system.

It will be appreciated that the precise form of the proximity sensor does not form part of the invention. Whilst a capacitance type sensor is described herein, other types could be used equally effectively including ultrasonic and infrared-based devices.

Referring now to Figure 2, the stairlift carriage/chair assembly 20 is depicted mounted on rail 18. As can be seen the assembly includes a chair back 30 and a chair base 32 mounted on carriage chassis 34. The chair also includes arm rests 36a and 36b. Mounted at the outer end of armrest 36a is a conventional hand control 38 by means of which a user seated in the chair may control the movement of the carriage/chair 20 along the rail 18.

Mounted in the forward part of the chair base 32 is the antenna 40 of the proximity sensor described above, signals from the antenna 40 being fed to proximity sensor circuit 42 and, in turn, to the main stairlift control unit 44 mounted in the carriage.

Also mounted on or adjacent to the chair base 32 are a pair of further sensors 46 and 47. The sensor 46 serves to detect the presence of a person seated in the chair, preferably by detecting load on the chair base 32 as would be imparted by a user sitting thereon. The sensor 47 serves to detect when the chair base 32 is folded up

into the position shown diagrammatically in Figure 5, by arranging one or more contacts within the folding mechanism which execute a switching function when the chair is folded.

The sensors and control unit are programmed to operate as follows:-

As described above, the proximity sensor of which antenna 40 is a principal part, serves to detect if a person is standing alongside the carriage chair assembly as is illustrated in Figure 3; or is in the course of mounting, or dismounting from, the chair as is illustrated in Figure 4. In either event, a signal is provided by the proximity sensor circuit 42 to the main operating control unit 44 of the stairlift and the landing controls 22 and 24 are isolated. This then prevents the carriage/chair assembly 20 being operated by a second user to whom, for example, the carriage/chair 20 is not visible.

In a similar manner the sensor 46 detects when the user is, or is not, seated in the chair, and renders the hand controls 38 inoperative when there is no user seated in the chair. This prevents movement of the carriage/chair 20 if the user inadvertently touches or leans on the controls 38 when mounting, or dismounting from, the chair.

The combination of sensors 40 and 46 also allows the stairlift to be controlled remotely by one user when another user is a passenger in the chair, a feature sometimes referred to as attendant control. In this event, when the sensor 46 detects that a user is seated in the chair, the isolation imposed by the proximity sensor is overridden and the carriage/chair 20 again falls under the control of call switches 22 and 24.

The sensor 47 serves to detect when the chair is folded into the position shown in Figure 5. When the chair is folded as shown in Figure 5, the proximity sensor described above may not operate in the desired manner. When the chair is folded the

antenna may experience a change of signal due to the presence of the chair back 30 (depending on the location of the sensor within the chair) and thus isolate the call switches 22 and 24. However, in practice, it is desirable for the carriage to be under the control of the landing controls 22 and 24, when the chair is in the folded configuration. Thus, by arranging for sensor 47 to determine when the chair is in the folded configuration, the isolation imposed by the proximity sensor may be overridden and the carriage and chair assembly 20 again left under the control of the landing controls 22 and 24.

It will thus be appreciated that the present invention, at least as included in the working embodiment described above, enhances stairlift safety whilst obviating the inconvenience arising from the use or misuse of conventional carriage holding switches currently provided on stairlift carriages.

Claims

1. A method of enhancing the safety of a stairlift installation having :-

a rail extending between an upper end and a lower end of a staircase;

a carriage moveable along said rail;

carriage operating controls remote from said carriage ,

said method being characterised in that a proximity sensor is provided which is operable to sense a person in the proximity of said carriage, and to render said carriage operating control inoperative.
2. A method as claimed in claim 1 including the step of mounting said proximity sensor on or about said carriage.
3. A method as claimed in claim 1 or claim 2 wherein a chair is mounted on said carriage, said method further including the step of providing an occupancy sensor to sense when load is applied to said chair.
4. A method as claimed in claim 3 wherein said chair is foldable, said method further including providing a sensor to sense when said chair is in the folded configuration.
5. A stairlift assembly having:

a rail extending between an upper and lower end of a staircase;

a carriage moveable along said rail; and

carriage operating controls remote from said carriage,

said apparatus being characterised in that a proximity sensor is provided, said proximity sensor being operable to sense the proximity of a person to said carriage and being further operable to, in the event of sensing such a person, rendering said carriage operation controls inoperative.

6. An assembly as claimed in claim 5 wherein said proximity sensor is mounted on or about said carriage.
7. An assembly as claimed in claim 5 or claim 6 further including a chair mounted on said carriage, at least part of said proximity sensor being mounted on said chair.
8. An assembly as claimed in any one of claims 5 to 7 wherein said proximity sensor is of the capacitance type.
9. An assembly as claimed in claim 7 or claim 8 further including an occupancy sensor operable to detect the presence of a user seated in said chair.
10. An assembly as claimed in claim 9 wherein said occupancy sensor comprises a load sensor operable to sense load on a chair base.
11. An assembly as claimed in any of claims 7 to 10 wherein said chair is foldable, said assembly further including a position sensor operable to sense when said chair is in the folded configuration.

12. A stairlift assembly including:

a rail;

a carriage mounted on said rail for movement there-along;

a chair mounted on said carriage;

at least one user operable control to cause movement of said carriage along said rail,


said assembly being characterised in that an occupancy sensor is provided to sense the presence of a user seated in said chair and to activate said user operable control only when a user is seated in said chair.

13. An assembly as claimed in claim 12 wherein said occupancy sensor comprises a load sensor incorporated in said chair and/or said carriage and operable to sense load applied by a user seated thereon.

ABSTRACT**SAFETY ENHANCEMENT FOR A STAIRLIFT**

The present invention enhances the safety of a stairlift by providing a proximity sensor 40, 42 to detect the proximity of users and other objects to a stairlift carriage 20 and to render remote call controls 22, 24 inoperative. A chair occupancy sensor may also be provided to prevent inadvertent operation of the main user control 38 when a user is mounting, or dismounting from, the stairlift.

(use Figure 2)

FIGURE 1




FIGURE 2




FIGURE 3

FIGURE 4





FIGURE 5.



**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☒ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.